io surface



| | Name IO SURFACE UL 20° 2700K WT Reference U2630110WT |
|--|---|
| | Reference U2630110WT Color Textured white |
| | Category SURFACE |
| | |
| and the second s | |
| | LIGHT SOURCE |
| | Type |
| Gross L | uminous flux Depending on Mounting Accessories Lm |
| Color | temperature 2700 K |
| Chrom | MacAdam Step 2 |
| Color Ren | ndering Index CRI>90 |
| | Power Depending on Mounting Accessories W |
| DIMENSIONS | Current Depending on Mounting Accessories mA |
| | LED lifespan L90B10>55.000h |
| | LIGHTING FIXTURE PHOTOMETRIC DATA |
| | ing efficiency 92% |
| | uminous flux 0 Lm |
| | t beam angle 20° |
| Ø1.42in Ø1.57in | |
| | |
| (36mm) (40mm) | |
| | LIGHTING FIXTURE ELECTRICAL DATA |
| 3.30in (84mm) | Driver Requires remote driver |
| $\longmapsto \qquad \longleftarrow$ | Driver Requires remote driver |
| 3.30in (84mm) | Driver Requires remote driver of the system W Frequency Depending on Mounting Accessories |
| 3.30in (84mm) | Driver Requires remote driver |
| 3,30in (84mm) Power values o | Driver Requires remote driver of the system W Frequency Depending on Mounting Accessories |
| 3.30in (84mm) Power values o | Driver Requires remote driver of the system W Frequency Depending on Mounting Accessories |
| ACCESORIES | Driver Requires remote driver of the system W Frequency Depending on Mounting Accessories Dimming Depending on Mounting Accessories |
| ACCESORIES | Driver Requires remote driver of the system W Frequency Depending on Mounting Accessories Dimming Depending on Mounting Accessories OTHER DATA |
| ACCESORIES ACCESORIES | Driver Requires remote driver of the system W Frequency Depending on Mounting Accessories Dimming Depending on Mounting Accessories OTHER DATA DAMP |
| ACCESORIES | Driver Requires remote driver of the system W Frequency Depending on Mounting Accessories Dimming Depending on Mounting Accessories OTHER DATA OTHER DATA ion box cover Included. For octogonal Junction box x cover color Textured white. Other finishing, please consult |
| ACCESORIES ACCESORIES MIXER DIFFUSER ANTI-GLARE HONEYCOMB LOUVER Junction boo Junction boo cover me | Driver Requires remote driver of the system W Frequency Depending on Mounting Accessories Dimming Depending on Mounting Accessories OTHER DATA OTHER DATA ental location DAMP ion box cover Included. For octogonal Junction box x cover color Textured white. Other finishing, please consult |
| ACCESORIES ACCESORIES MIXER DIFFUSER ANTI-GLARE HONEYCOMB LOUVER Junction box cover me | Driver Requires remote driver of the system W Frequency Depending on Mounting Accessories Dimming Depending on Mounting Accessories OTHER DATA OTHER DATA ental location DAMP ion box cover Included. For octogonal Junction box x cover color Textured white. Other finishing, please consult gessurements Ø5.51 in Ø140 mm |
| ACCESORIES ACCESORIES IXER DIFFUSER ANTI-GLARE HONEYCOMB LOUVER Junction box cover me | Driver Requires remote driver of the system W Frequency Depending on Mounting Accessories Dimming Depending on Mounting Accessories OTHER DATA DAMP ion box cover Included. For octogonal Junction box x cover color Textured white. Other finishing, please consult Swivel angle 325° |
| ACCESORIES ACCESORIES MIXER DIFFUSER ANTI-GLARE HONEYCOMB LOUVER Junction bo Junction box cover me Reference Refer | Driver Requires remote driver of the system W Frequency Depending on Mounting Accessories Dimming Depending on Mounting Accessories OTHER DATA OTHER DATA ental location DAMP ion box cover Included. For octogonal Junction box x cover color Textured white. Other finishing, please consult Basurements 95.51 in Ø140 mm Swivel angle 325° otation angle 355° |
| ACCESORIES ACCESORIES MIXER DIFFUSER ANTI-GLARE HONEYCOMB LOUVER Junction box cover me Reference Referen | Driver Requires remote driver of the system W Frequency Depending on Mounting Accessories Dimming Depending on Mounting Accessories OTHER DATA OTHER DATA ental location DAMP ion box cover Included. For octogonal Junction box x cover color Textured white. Other finishing, please consult seasurements Ø5.51 in Ø140 mm Swivel angle 325° otation angle 355° Weight 0.76 lb 343 gr |
| ACCESORIES ACCESORIES MIXER DIFFUSER ANTI-GLARE HONEYCOMB LOUVER Junction box cover me Reference Referen | Driver Requires remote driver of the system W Frequency Depending on Mounting Accessories Dimming Depending on Mounting Accessories OTHER DATA OTHER DATA ion box cover Included. For octogonal Junction box x cover color Textured white. Other finishing, please consult gasurements Ø5.51 in Ø140 mm Swivel angle 325° otation angle 355° Weight 0.76 tb 343 gr 0.93 tb 423 gr |

IO is a LED spotlight miniaturised in a fixture that is so small that it fits on the palm of your hand. Designed for accent lighting applications, its small dimensions mean it can be fitted in display cabinets, shop windows and small places without generating an invasive presence on the scene.

JOKERLIGHT LLC 2750 NW 84th Ave · Doral · FL 33122 (USA) Info@jokerlight.com · www.jokerlight.com

PREMIO ADCV 2017 ORO ΠF

15-05-25/02:41







PRODUCT

| Model |
|-----------|
| Reference |
| Category |


| PRODUCT |
|--|
| Beam Mixer Diffuser |
| 0805-01-00 |
| Accessories |
| NOT SOLD SEPARATELY AFFECTS THE LIGHTING PARAMETERS |

The Beam Mixer Diffuser is used to smooth beam artifacts caused by parabolic, Fresnel, or TIR lens collimators without significant broadening.

The unique mixing design provides superior far-field smoothing and color mixing with high on-axis brightness. Compared with traditional diffusers, it maintains higher central beam candlepower (CBCP), and produce less undesirable "field light" at higher angles.







PRODUCT

| Model |
|-----------|
| Reference |
| Colour |
| Category |

| PRODUCT | |
|---|----------|
| Anti-glare Honeycomb Louver | |
| 0806-00-00 WT NT | |
| WT □ Textured white NT ■ Textured black | |
| Accessories | |
| NOT SOLD SEPARATELY | A |
| AFFECTS THE LIGHTING PARAMETERS | \odot |

Accessory made up of louver in the shape of a honeycomb panel to reduce glare and the effects of direct rays of vision.

