## io surface



		PRODUCT
	Name	IO SURFACE UL 20º 3000K WT
	Reference	U2630111WT
	Color	Textured white
	Category	SURFACE
ALL		
		LIGHT SOURCE
	Туре	LED
	Gross luminous flux	Depending on Mounting Accessories Lm
	Color temperature	3000 K
	Chromatic stability	MacAdam Step 2
	Color Rendering Index	CRI>90
	Power	Depending on Mounting Accessories W
	Current	Depending on Mounting Accessories mA
DIMENSIONS	LED lifespan	L90B10>55.000h
	Lighting efficiency	PROFESSION PROFES
		LIGHTING FIXTURE   PHOTOMETRIC DATA
2.75in (70mm)	Delivered luminous flux	0 Lm
	Light beam angle	20°
Ø1.42in Ø1.57in		
Ø1.42in Ø1.57in (36mm) (40mm) 3.30in (84mm)	Driver	LIGHTING FIXTURE   ELECTRICAL DATA
Ø1.42in Ø1.57in (36mm) (40mm)	Driver Power values of the system	
Ø1.42in Ø1.57in (36mm) (40mm)		Requires remote driver
Ø1.42in Ø1.57in (36mm) 40mm) 3.30in (84mm)	Power values of the system	Requires remote driver W
Ø1.42in Ø1.57in (36mm) (40mm)	Power values of the system Frequency	Requires remote driver W Depending on Mounting Accessories
01.42in 01.57in (36mm) 40mm) 3.30in (84mm)	Power values of the system Frequency	Requires remote driver W Depending on Mounting Accessories
Ø1.42in Ø1.57in (36mm) (40mm) 3.30in (84mm)	Power values of the system Frequency	Requires remote driver W Depending on Mounting Accessories Depending on Mounting Accessories
Ø1.42in Ø1.57in (36mm) (40mm) 3.30in (84mm) ACCESORIES	Power values of the system Frequency Dimming	Requires remote driver W Depending on Mounting Accessories Depending on Mounting Accessories OTHER DATA
01.42in 01.57in (36mm) (40mm) 3.30in (84mm) ACCESORIES	Power values of the system Frequency Dimming Environmental location	Requires remote driver W Depending on Mounting Accessories Depending on Mounting Accessories OTHER DATA DAMP
Ø1.42in Ø1.57in (36mm) (40mm) 3.30in (84mm) ACCESORIES	Power values of the system Frequency Dimming Environmental location Junction box cover	Requires remote driver W Depending on Mounting Accessories Depending on Mounting Accessories OTHER DATA DAMP Included. For octogonal Junction box
01.42in 01.57in (36mm) (40mm) 3.30in (84mm) ACCESORIES	Power values of the system Frequency Dimming Environmental location Junction box cover Junction box cover color	Requires remote driver W Depending on Mounting Accessories Depending on Mounting Accessories OTHER DATA DAMP Included. For octogonal Junction box Textured white. Other finishing, please consult
01.42in 01.57in (36mm) (40mm) 3.30in (84mm) ACCESORIES IXER DIFFUSER ANTI-GLARE HONEYCOMB	Power values of the system Frequency Dimming Environmental location Junction box cover Junction box cover color Junction box cover measurements	Requires remote driver W Depending on Mounting Accessories Depending on Mounting Accessories OTHER DATA DAMP Included. For octogonal Junction box Textured white. Other finishing, please consult Ø5.51 in   Ø140 mm
Ø1.42in Ø1.57in (40mm) 3.30in (84mm) ACCESORIES ACCESORIES ANTI-GLARE HONEYCOMB	Power values of the system Frequency Dimming Environmental location Junction box cover Junction box cover color Junction box cover measurements Swivel angle	Requires remote driver W Depending on Mounting Accessories Depending on Mounting Accessories OTHER DATA DAMP Included. For octogonal Junction box Textured white. Other finishing, please consult Ø5.51 in   Ø140 mm 325°
Ø1.42in Ø1.57in [36mm] [40mm] 3.30in [84mm] ACCESORIES ACCESORIES ANTI-GLARE HONEYCOMB	Power values of the system Frequency Dimming Environmental location Junction box cover Junction box cover color Junction box cover measurements Swivel angle Rotation angle	Requires remote driver W Depending on Mounting Accessories Depending on Mounting Accessories OTHER DATA DAMP Included. For octogonal Junction box Textured white. Other finishing, please consult Ø5.51 in   Ø140 mm 325° 355°
01.42in 01.57in (36mm) (40mm) 3.30in (84mm) ACCESORIES	Power values of the system Frequency Dimming Environmental location Junction box cover Junction box cover color Junction box cover measurements Swivel angle Rotation angle Weight Packaged weight	Requires remote driver W Depending on Mounting Accessories Depending on Mounting Accessories OTHER DATA DAMP Included. For octogonal Junction box Textured white. Other finishing, please consult Ø5.51 in   Ø140 mm 325° 355° 0.76 lb   343 gr
Ø1.42in Ø1.57in (36mm) (40mm) 3.30in (84mm) ACCESORIES	Power values of the system Frequency Dimming Environmental location Junction box cover Junction box cover color Junction box cover measurements Swivel angle Rotation angle Weight	Requires remote driver         W         Depending on Mounting Accessories         Depending on Mounting Accessories         OTHER DATA         DAMP         Included. For octogonal Junction box         Textured white. Other finishing, please consult         Ø5.51 in   Ø140 mm         325°         355°         0.76 lb   343 gr         0.93 lb   423 gr

IO is a LED spotlight miniaturised in a fixture that is so small that it fits on the palm of your hand. Designed for accent lighting applications, its small dimensions mean it can be fitted in display cabinets, shop windows and small places without generating an invasive presence on the scene.

JOKERLIGHT LLC 2750 NW 84th Ave · Doral · FL 33122 (USA) Info@jokerlight.com · www.jokerlight.com

PREMIO ADCV 2017 ORO ΠF

15-05-25/02:41







## PRODUCT

Model
Reference
Category


PRODUCT
Beam Mixer Diffuser
0805-01-00
Accessories
NOT SOLD SEPARATELY AFFECTS THE LIGHTING PARAMETERS

The Beam Mixer Diffuser is used to smooth beam artifacts caused by parabolic, Fresnel, or TIR lens collimators without significant broadening.

The unique mixing design provides superior far-field smoothing and color mixing with high on-axis brightness. Compared with traditional diffusers, it maintains higher central beam candlepower (CBCP), and produce less undesirable "field light" at higher angles.







## PRODUCT

Model
Reference
Colour
Category

PRODUCT	
Anti-glare Honeycomb Louver	
0806-00-00   WT   NT	
WT □ Textured white   NT ■ Textured black	
Accessories	
NOT SOLD SEPARATELY	<b>A</b>
AFFECTS THE LIGHTING PARAMETERS	$\odot$

Accessory made up of louver in the shape of a honeycomb panel to reduce glare and the effects of direct rays of vision.

