




DIMENSIONS



AWARDS



Name	BLACK FOSTER TRI 5 UL SPOT 3000K NMG
Reference	U3184111NMG
Color	Matt black-Metallized gold
Category	CEILING RECESSED
Type	LED
Gross luminous flux	Depending on Mounting Accessories Lm
Color temperature	3000 K
Chromatic stability	MacAdam Step 3
Color Rendering Index	CRI>90
Power	Depending on Mounting Accessories W
Current	Depending on Mounting Accessories mA
LED lifespan	L90B10>102.000h
Lighting efficiency	90%
Delivered luminous flux	0 Lm
Light beam angle	19°
Driver	Requires remote driver
Power values of the system	W
Frequency	Depending on Mounting Accessories
Dimming	Depending on Mounting Accessories
IC Rated	Yes
Environmental location	DAMP
Recess measurements	1.97 x 8.75 50 x 222
Weight	0.78 lb 354 gr
Packaged weight	1.03 lb 469 gr
Packaging dimensions	11.61x6.10x2.87 in 295x155x73 mm
Materials	Aluminium - Acrylonitrile Butadiene Styrene - Polycarbonate

PRODUCT

LIGHT SOURCE

LIGHTING FIXTURE | PHOTOMETRIC DATA

LIGHTING FIXTURE | ELECTRICAL DATA

OTHER DATA




Black Foster is our lineal recessed luminaire with "The invisible black" effect, also available in a trimless version. Hiding the source of light, Black Foster stands out for its visual comfort and its elegance.

POLAR DIAGRAM



CONICAL DIAGRAM



UGR

Glare Evaluation According to UGR										
ρ Ceiling	70	70	50	50	30	70	70	50	50	30
ρ Walls	50	30	50	30	30	50	30	50	30	30
ρ Floor	20	20	20	20	20	20	20	20	20	20
Room Size X Y	Viewing direction at right angles to lamp axis					Viewing direction parallel to lamp axis				
2H 2H	2.2	2.9	2.5	3.1	3.3	3.1	3.8	3.3	3.9	4.1
3H 3H	5.7	6.3	6.0	6.6	6.8	7.0	7.6	7.3	7.8	8.1
4H 4H	7.7	8.3	8.0	8.5	8.8	8.8	9.4	9.1	9.7	9.9
6H 6H	9.9	10.5	10.3	10.7	11.0	11.1	11.6	11.4	11.9	12.2
8H 8H	11.1	11.6	11.4	11.9	12.2	12.3	12.9	12.7	13.1	13.4
12H 12H	12.5	13.0	12.8	13.3	13.6	13.8	14.3	14.1	14.6	14.9
4H 2H	3.6	4.2	3.9	4.4	4.7	4.2	4.7	4.5	5.0	5.3
3H 3H	7.3	7.8	7.7	8.1	8.4	8.2	8.7	8.5	9.0	9.3
4H 4H	9.4	9.8	9.8	10.2	10.5	10.2	10.6	10.6	11.0	11.3
6H 6H	11.7	12.1	12.1	12.4	12.8	12.7	13.0	13.1	13.4	13.7
8H 8H	12.9	13.2	13.3	13.6	14.0	14.0	14.3	14.4	14.7	15.1
12H 12H	14.4	14.7	14.8	15.1	15.5	15.5	15.8	16.0	16.2	16.6
8H 4H	10.4	10.7	10.8	11.1	11.5	11.0	11.3	11.4	11.7	12.1
6H 6H	12.8	13.1	13.3	13.5	13.9	13.6	13.9	14.1	14.3	14.7
8H 8H	14.3	14.5	14.7	14.9	15.4	15.2	15.3	15.6	15.8	16.3
12H 12H	15.9	16.1	16.4	16.5	17.0	16.9	17.1	17.4	17.5	18.0
12H 4H	10.7	10.9	11.1	11.3	11.7	11.2	11.5	11.6	11.9	12.3
6H 6H	13.2	13.4	13.7	13.8	14.3	13.9	14.1	14.4	14.5	15.0
8H 8H	14.8	14.9	15.2	15.4	15.9	15.5	15.7	16.0	16.2	16.7
Variation of the observer position for the luminaire distances S										
S = 1.0H	+0.2 / -0.1					+0.2 / -0.1				
S = 1.5H	+0.3 / -0.3					+0.3 / -0.3				
S = 2.0H	+0.5 / -0.5					+0.5 / -0.5				
Standard table	---					---				
Correction Summand	---					---				
Corrected Glare Indices referring to 1050lm Total Luminous Flux										

GUÍA DE INSTALACIÓN



<https://youtu.be/SVWNEfbfVY>