BLACK FOSTER

٥) (

0

DIMENSIONS

3.82in (97mm) 1.73in (44mm)

 \odot

۲

0

16.97in (431mm)

57in (40m



Reference	
Color	-
Category	-
Туре	-
Gross luminous flux	_
Color temperature	
Chromatic stability	-
Color Rendering Index	
Power	-
Current	-
LED lifespan	_
Lighting efficiency Delivered luminous flux	-
	-
Delivered luminous flux	-
Delivered luminous flux Light beam angle	-
Delivered luminous flux Light beam angle Driver	-
Delivered luminous flux Light beam angle Driver Power values of the system	- - - - -
Delivered luminous flux Light beam angle Driver Power values of the system Frequency	-
Delivered luminous flux Light beam angle Driver Power values of the system Frequency	-
Delivered luminous flux Light beam angle Driver Power values of the system Frequency Dimming	-
Delivered luminous flux Light beam angle Driver Power values of the system Frequency Dimming	-
Delivered luminous flux Light beam angle Driver Power values of the system Frequency Dimming IC Rated Environmental location	-
Delivered luminous flux Light beam angle Driver Power values of the system Frequency Dimming IC Rated Environmental location Recess measurements	-
Delivered luminous flux Light beam angle Driver Power values of the system Frequency Dimming IC Rated Environmental location Recess measurements Weight	-

LIGHT SOURCE

LED
Depending on Mounting Accessories Lm
3000 K
MacAdam Step 3
CRI>90
Depending on Mounting Accessories W
Depending on Mounting Accessories mA
L90B10>102.000h

LIGHTING FIXTURE | PHOTOMETRIC DATA

92%		
0 Lm		
38°		

LIGHTING FIXTURE | ELECTRICAL DATA

OTHER DATA

es	
AMP	
97 x 17.20 50 x 437	
51 lb 684 gr	
.22 lb 1009 gr	
4.13x22.83 in Ø105x580 mm	
luminium - Acrylonitrile Butadiene Styrene - Polycarbo	onate







Black Foster is our lineal recessed luminaire with "The invisible black" effect, also available in a trimless version. Hiding the source of light, Black Foster stands out for its visual comfort and its elegance.

