




DIMENSIONS



Name	BLACK FOSTER REC 5 UL FLOOD 4000K NMG
Reference	U3194012NMG
Color	Matt black-Metallized gold
Category	CEILING RECESSED

PRODUCT

Type	LED
Gross luminous flux	Depending on Mounting Accessories Lm
Color temperature	4000 K
Chromatic stability	MacAdam Step 3
Color Rendering Index	CRI>90
Power	Depending on Mounting Accessories W
Current	Depending on Mounting Accessories mA
LED lifespan	L80B10 >60.000h

LIGHT SOURCE

Lighting efficiency	92%
Light beam angle	38°

LIGHTING FIXTURE | PHOTOMETRIC DATA

Driver	Requires remote driver
Power values of the system	W
Dimming	Depending on Mounting Accessories

LIGHTING FIXTURE | ELECTRICAL DATA

Environmental location	DAMP
Weight	0.75 lb 340 gr
Packaged weight	0.96 lb 435 gr
Packaging dimensions	10.35x4.09x2.17 in 263x104x55 mm
Units per package	1
Materials	Aluminium / Acrylonitrile Butadiene Styrene

OTHER DATA




AWARDS




Black Foster is the product that transfers the claimed effect "The Invisible Black" to a recessed-isolated lineal luminary; also available in trimless version. If we take a closer view to the recessed model, its bezel is so thin that when lighted up, it is unperceived; offering an aesthetic of "visual trimless". Black Foster stands out for its refinement, its visual comfort and for almost completely hide the source of light from the human eye range.

POLAR DIAGRAM



CONICAL DIAGRAM



UGR

Glare Evaluation According to UGR											
ρ Ceiling	70	70	50	50	30	70	70	50	50	30	30
ρ Walls	50	30	50	30	30	50	30	50	30	30	30
ρ Floor	20	20	20	20	20	20	20	20	20	20	20
Room Size X Y		Viewing direction at right angles to lamp axis					Viewing direction parallel to lamp axis				
2H	2H	-14.2	-13.6	-14.0	-13.4	-13.2	-15.1	-14.5	-14.9	-14.3	-14.1
	3H	-8.0	-7.4	-7.7	-7.2	-6.9	-7.8	-7.2	-7.6	-7.0	-6.8
	4H	-4.5	-3.9	-4.2	-3.7	-3.4	-3.9	-3.4	-3.6	-3.1	-2.8
	6H	-0.8	-0.3	-0.5	-0.0	0.3	-0.4	0.1	-0.1	0.3	0.6
	8H	1.0	1.5	1.4	1.8	2.1	1.4	1.9	1.7	2.1	2.4
	12H	3.0	3.5	3.4	3.8	4.1	3.4	3.9	3.7	4.2	4.5
4H	2H	-11.7	-11.1	-11.4	-10.9	-10.6	-12.1	-11.5	-11.8	-11.3	-11.0
	3H	-5.7	-5.3	-5.4	-5.0	-4.7	-5.6	-5.1	-5.2	-4.8	-4.5
	4H	-2.3	-1.9	-1.9	-1.6	-1.2	-1.9	-1.5	-1.5	-1.1	-0.8
	6H	1.3	1.6	1.7	1.9	2.3	1.6	1.9	2.0	2.2	2.6
	8H	3.1	3.4	3.5	3.8	4.2	3.4	3.7	3.8	4.1	4.5
	12H	5.2	5.4	5.6	5.8	6.2	5.5	5.7	5.9	6.1	6.6
8H	4H	-0.8	-0.5	-0.4	-0.1	0.3	-0.5	-0.2	-0.1	0.2	0.6
	6H	2.9	3.1	3.3	3.5	4.0	3.1	3.3	3.5	3.7	4.2
	8H	4.8	5.0	5.3	5.5	5.9	5.0	5.2	5.5	5.7	6.1
	12H	7.0	7.2	7.5	7.6	8.1	7.3	7.4	7.8	7.9	8.4
12H	4H	-0.3	-0.0	0.2	0.4	0.8	-0.0	0.2	0.4	0.6	1.1
	6H	3.5	3.6	3.9	4.1	4.6	3.6	3.8	4.1	4.3	4.7
	8H	5.5	5.7	6.0	6.1	6.6	5.7	5.9	6.2	6.3	6.8
Variation of the observer position for the luminaire distances S											
S = 1.0H	+0.9 / -0.3					+1.3 / -0.4					
S = 1.5H	+1.9 / -0.6					+2.7 / -0.7					
S = 2.0H	+3.1 / -0.8					+4.2 / -1.0					
Standard table Correction Summand	---					---					
Corrected Glare Indices referring to 825lm Total Luminous Flux											