



DIMENSIONS



ACCESSORIES



TRACK 48V OPTIONS

AWARDS



PRODUCT

Name SIX S 48V UL DIM DALI 17° 3000K WTW

Reference U3330211WTW

Color Textured white - White track

Category TRACKLIGHTS

LIGHT SOURCE

Type LED

Gross luminous flux 1070 Lm

Color temperature 3000 K

Chromatic stability MacAdam Step 2

Color Rendering Index CRI>90

Power 8.5 W

Current 500 mA

Efficacy 126 Lm/W

LED lifespan L80B10 >60.000h

LIGHTING FIXTURE | PHOTOMETRIC DATA

Lighting efficiency 86%

Light beam angle 17°

LIGHTING FIXTURE | ELECTRICAL DATA

Driver Included

Power values of the system 9,00 W

Dimming DALI

OTHER DATA

DAMP

Swivel angle 310°

Rotation angle 360°

Track type Track 48V

Weight 0.36 lb | 164 gr

Packaged weight 0.46 lb | 210 gr

Packaging dimensions 7.48x5.71x0.94 in | 190x145x24 mm

Units per package 1


Materials Aluminium - Polycarbonate




Environmental location	DAMP
Swivel angle	310°
Rotation angle	360°
Track type	Track 48V
Weight	0.36 lb 164 gr
Packaged weight	0.46 lb 210 gr
Packaging dimensions	7.48x5.71x0.94 in 190x145x24 mm
Units per package	1
Materials	Aluminium - Polycarbonate


Six 48V is a family of spotlights for low voltage tracklight applications that stands out for its lightness and elegance. Available in L, M, S, and XS, its body; disk looking, rounded shaped, encloses an innovative combination of reflector and lens. The combined action of both, allows Six to direct light rays with the maximum uniformity in a very small distance that, at the same time, has made possible its differential design-reduced and minimalist-. In addition, Six can be freely articulated due to its airy arm which allows the spotlight to be orientated in any direction.

POLAR DIAGRAM



CONICAL DIAGRAM





TRACK 48V TRIMLESS UL

TRACK 48V TRIMLESS 3.28ft (1m) UL	U338-01-00-	N	WT
TRACK 48V TRIMLESS 6.56ft (2m) UL	U338-02-00-	N	WT
TRACK 48V TRIMLESS Corner 90° One Plane UL	U338-06-00-	N	WT
TRACK 48V TRIMLESS Corner 90° Two Planes UL	U338-07-00-	N	WT

PLASTERBOARD CEILING MANDATORY THICKNESS 0.50in (12.5mm)
RECOMMENDED FOR INSTALLATIONS WHERE THE PROFILE CAN BE INSTALLED BEFORE THE FALSE PLASTERBOARD CEILING

TRACK 48V TRIMLESS
Corner 90° One Plane UL



*Electrical connection not included

TRACK 48V TRIMLESS
Corner 90° Two Planes UL



*Electrical connection not included

TRIMLESS INSTALLATION GUIDE
<https://youtu.be/SVWNEfblfVY>



TRACK 48V SURFACE UL

TRACK 48V SURFACE 3.28ft (1m) UL	U338-11-00-	NT	WT
TRACK 48V SURFACE 6.56ft (2m) UL	U338-12-00-	NT	WT
TRACK 48V SURFACE Corner 90° One Plane UL	U338-14-00-	NT	WT

TRACK 48V SURFACE
Corner 90° One Plane UL



*Electrical connection not included



TRACK 48V SURFACE SHORT UL

TRACK 48V SURFACE SHORT 3.28ft (1m) UL	U338-21-00-	NT	WT
TRACK 48V SURFACE SHORT 6.56ft (2m) UL	U338-22-00-	NT	WT
TRACK 48V SURFACE SHORT Corner 90° One Plane UL	U338-24-00-	NT	WT

TRACK 48V SURFACE SHORT
Corner 90° One Plane UL



*Electrical connection not included



	P	V	D
CONSTANT VOLTAGE LED POWER SUPPLY	U100-00-78	96W	48V
			8.16 x 2.97 x 1.30 in 207 x 75.4 x 33 mm

120 & 277 V | 50/60 Hz

UL DROP VOLTAGE TABLE

POWER	CABLE SECTION	CABLE LENGTH			
		16.40ft	32.80ft	65.62ft	98.43ft
96W	AWG 16	5m	10m	20m	30m
		164ft	164ft	131.32ft	82ft
		50m	50m	40m	25m

ALL 48V TRACK UL



Live-End Connector 48V
A338-00-01- | N | W |



L-JOINT Connector 48V UL
U338-00-12- | N | W |



Corner 90° Connector One Plane 48V
A338-00-24- | N | W |


*Not suitable for trimless version



Central Connector 48V
A338-00-02- | N | W |



Wireless Control 48V
0434-01-31- | N | W |
Casambi/AAG Stucchi App



Cover Gap 3,28 ft (1m) 48V UL
U0338-00-30- | N |

TRIMLESS 48V UL



Trimless T-Bracket 48V
A338-00-03



Clamp for M6 ROD
A338-00-09
*See accessories quantities



Trimless Long T-Bracket 48V
A338-00-04




Track Clamp
A338-00-10
*See accessories quantities



Trimless Straight Joiners 48V (2 units)
A338-00-05- | N | WT |




Suspension Kit
A338-00-08
*See accessories quantities



**Trimless Plaster Installation Guard
3.28ft (1m) 48V UL**
U338-00-21

*** SUGGESTED MOUNTING ACCESSORIES QUANTITIES**
3.28ft (1000mm) - 2 Pcs.
6.56ft (2000mm) - 3 Pcs.

SURFACE, SUSPENSION , SURFACE SHORT & SUSPENSION SHORT 48V UL



Surface Straight Joiner 48V
A338-00-11

TRIMLESS, SURFACE & SUSPENSION 48V UL



End 48V UL

U338-00-06- | NT | WT |



End feed 48V UL

U338-00-07- | NT | WT |

SURFACE SHORT & SUSPENSION SHORT 48V UL



Short End 48V UL

U338-00-18- | NT | WT |



Short End feed 48V UL

U338-00-19- | NT | WT |

SUSPENSION & SUSPENSION SHORT 48V UL



Suspension Kit 48V (2 units)

A338-00-15- | NT | WT |



Suspension feed Kit 48V UL

U338-00-17- | N | W |



*For remote power supply