




### DIMENSIONS



### ACCESSORIES



TRACK 48V OPTIONS

### AWARDS



### PRODUCT

|           |  |
|-----------|--|
| Name      | SIX XS 48V SHORT UL DIM DALI 17° 3000K NTW |
| Reference | U3350211NTW-S                              |
| Color     | Textured black - White track               |
| Category  | TRACKLIGHTS                                |

### LIGHT SOURCE

|                       |                 |
|-----------------------|-----------------|
| Type                  | LED             |
| Gross luminous flux   | 500 Lm          |
| Color temperature     | 3000 K          |
| Chromatic stability   | MacAdam Step 2  |
| Color Rendering Index | CRI>90          |
| Power                 | 4.5 W           |
| Current               | 500 mA          |
| Efficacy              | 111 Lm/W        |
| LED lifespan          | L80B10 >60,000h |

### LIGHTING FIXTURE | PHOTOMETRIC DATA

|                     |     |
|---------------------|-----|
| Lighting efficiency | 90% |
| Light beam angle    | 17° |

### LIGHTING FIXTURE | ELECTRICAL DATA

|                            |          |
|----------------------------|----------|
| Driver                     | Included |
| Power values of the system | 5,00 W   |
| Dimming                    | DALI     |

### OTHER DATA

|                        |                                   |
|------------------------|-----------------------------------|
| Environmental location | DAMP                              |
| Swivel angle           | 310°                              |
| Rotation angle         | 360°                              |
| Track type             | Track 48V                         |
| Weight                 | 0.25 lb   112 gr                  |
| Packaged weight        | 0.35 lb   160 gr                  |
| Packaging dimensions   | 7.48x5.71x0.94 in   190x145x24 mm |
| Units per package      | 1                                 |
| Materials              | Aluminium - Polycarbonate         |




Six 48V is a family of spotlights for low voltage tracklight applications that stands out for its lightness and elegance. Available in L, M, S, and XS, its body; disk looking, rounded shaped, encloses an innovative combination of reflector and lens. The combined action of both, allows Six to direct light rays with the maximum uniformity in a very small distance that, at the same time, has made possible its differential design-reduced and minimalist-. In addition, Six can be freely articulated due to its airy arm which allows the spotlight to be orientated in any direction.

POLAR DIAGRAM



CONICAL DIAGRAM





TRACK 48V TRIMLESS UL

|   |             |   |    |
|---|-------------|---|----|
| TRACK 48V TRIMLESS 3.28ft (1m) UL           | U338-01-00- | N | WT |
| TRACK 48V TRIMLESS 6.56ft (2m) UL           | U338-02-00- | N | WT |
| TRACK 48V TRIMLESS Corner 90° One Plane UL  | U338-06-00- | N | WT |
| TRACK 48V TRIMLESS Corner 90° Two Planes UL | U338-07-00- | N | WT |

PLASTERBOARD CEILING MANDATORY THICKNESS 0.50in (12.5mm)  
RECOMMENDED FOR INSTALLATIONS WHERE THE PROFILE CAN BE INSTALLED BEFORE THE FALSE PLASTERBOARD CEILING

TRACK 48V TRIMLESS  
Corner 90° One Plane UL



\*Electrical connection not included

TRACK 48V TRIMLESS  
Corner 90° Two Planes UL



\*Electrical connection not included

TRIMLESS INSTALLATION GUIDE  
<https://youtu.be/SVWNEfblfVY>



TRACK 48V SURFACE UL

|   |             |    |    |
|---|-------------|----|----|
| TRACK 48V SURFACE 3.28ft (1m) UL          | U338-11-00- | NT | WT |
| TRACK 48V SURFACE 6.56ft (2m) UL          | U338-12-00- | NT | WT |
| TRACK 48V SURFACE Corner 90° One Plane UL | U338-14-00- | NT | WT |

TRACK 48V SURFACE  
Corner 90° One Plane UL



\*Electrical connection not included



TRACK 48V SURFACE SHORT UL

|   |             |    |    |
|---|-------------|----|----|
| TRACK 48V SURFACE SHORT 3.28ft (1m) UL          | U338-21-00- | NT | WT |
| TRACK 48V SURFACE SHORT 6.56ft (2m) UL          | U338-22-00- | NT | WT |
| TRACK 48V SURFACE SHORT Corner 90° One Plane UL | U338-24-00- | NT | WT |

TRACK 48V SURFACE SHORT  
Corner 90° One Plane UL



\*Electrical connection not included



|  |                   | P   | V   | D   |
|--|-------------------|-----|-----|---|
| <b>CONSTANT VOLTAGE LED POWER SUPPLY</b> | <b>U100-00-78</b> | 96W | 48V | 8.16 x 2.97 x 1.30 in<br>207 x 75.4 x 33 mm |

120 & 277 V | 50/60 Hz

UL DROP VOLTAGE TABLE

| POWER | CABLE SECTION | CABLE LENGTH  |                |                |                |
|-------|---------------|---------------|----------------|----------------|----------------|
|       |               | 16.40ft<br>5m | 32.80ft<br>10m | 65.62ft<br>20m | 98.43ft<br>30m |
| 96W   | AWG 16        | 164ft         | 164ft          | 131.32ft       | 82ft           |
|       |               | 50m           | 50m            | 40m            | 25m            |

ALL 48V TRACK UL



**Live-End Connector 48V**  
A338-00-01- | N | W |



**L-JOINT Connector 48V UL**  
U338-00-12- | N | W |



**Corner 90° Connector One Plane 48V**  
A338-00-24- | N | W |

\*Not suitable for trimless version



**Central Connector 48V**  
A338-00-02- | N | W |



**Wireless Control 48V**  
0434-01-31- | N | W |  
Casambi/AAG Stucchi App



**Cover Gap 3,28 ft (1m) 48V UL**  
U0338-00-30- | N |

TRIMLESS 48V UL



**Trimless T-Bracket 48V**  
A338-00-03



**Clamp for M6 ROD**  
A338-00-09  
\*See accessories quantities



**Trimless Long T-Bracket 48V**  
A338-00-04



**Track Clamp**  
A338-00-10  
\*See accessories quantities



**Trimless Straight Joiners 48V (2 units)**  
A338-00-05- | N | WT |



**Suspension Kit**  
A338-00-08  
\*See accessories quantities



**Trimless Plaster Installation Guard  
3.28ft (1m) 48V UL**  
U338-00-21

**\* SUGGESTED MOUNTING ACCESSORIES QUANTITIES**  
3.28ft (1000mm) - 2 Pcs.  
6.56ft (2000mm) - 3 Pcs.

SURFACE, SUSPENSION , SURFACE SHORT & SUSPENSION SHORT 48V UL



**Surface Straight Joiner 48V**  
A338-00-11

TRIMLESS, SURFACE & SUSPENSION 48V UL



End 48V UL

U338-00-06- | NT | WT |



End feed 48V UL

U338-00-07- | NT | WT |

SURFACE SHORT & SUSPENSION SHORT 48V UL



Short End 48V UL

U338-00-18- | NT | WT |



Short End feed 48V UL

U338-00-19- | NT | WT |

SUSPENSION & SUSPENSION SHORT 48V UL




Suspension Kit 48V (2 units)

A338-00-15- | NT | WT |



Suspension feed Kit 48V UL

U338-00-17- | N | W |  DIM

\*For remote power supply