


BLACK FOSTER SURFACE

JOKERLIGHT®



DIMENSIONS



AWARDS



PRODUCT

Name	BLACK FOSTER SURF 10 UL SPOT 3500K NT
Reference	U3205113NT
Color	Textured black
Category	SURFACE

LIGHT SOURCE

Type	LED
Gross luminous flux	2300 Lm
Color temperature	3500 K
Chromatic stability	MacAdam Step 3
Color Rendering Index	CRI>90
Power	21 W
Current	700 mA
Efficacy	109 Lm/W
LED lifespan	L80B10 >60.000h

LIGHTING FIXTURE | PHOTOMETRIC DATA

Lighting efficiency	90%
Delivered luminous flux	2070 Lm
Light beam angle	19°

LIGHTING FIXTURE | ELECTRICAL DATA

Driver	Included: ERP-PSB series or similar
Power values of the system	24,00 W
Frequency	50/60 Hz
Dimming	0-10V / TRIAC/ELV dimming only at 120V

OTHER DATA


Environmental location	DAMP
Junction box cover	Included. For octagonal Junction box
Junction box cover color	Textured white. Other finishing, please consult
Junction box cover measurements	Ø4.33 in Ø110 mm
Weight	3.36 lb 1524 gr
Packaged weight	4.70 lb 2134 gr
Packaging dimensions	Ø5.04x20.28 in Ø128x515 mm
Materials	Aluminium - Acrylonitrile Butadiene Styrene - Polycarbonate




Black Foster Surface is the product that transfers the claimed effect "The Invisible Black" to a linear system in surface application. Black Foster has a very discrete presence in the interior design due to its reduced dimensions and its extremely low glare helping the piece not to gain much prominence.



POLAR DIAGRAM



CONICAL DIAGRAM



UGR

Glare Evaluation According to UGR												
ρ Ceiling		70	70	50	50	30	70	70	50	50	30	30
ρ Walls		50	30	50	30	30	50	30	50	30	30	30
ρ Floor		20	20	20	20	20	20	20	20	20	20	20
Room Size X Y		Viewing direction at right angles to lamp axis					Viewing direction parallel to lamp axis					
2H	2H	3.2	3.8	3.4	4.0	4.2	3.7	4.4	3.9	4.5	4.7	
	3H	6.4	7.0	6.6	7.2	7.4	7.2	7.8	7.4	8.0	8.2	
	4H	8.2	8.8	8.5	9.0	9.3	9.1	9.7	9.4	10.0	10.2	
	6H	10.3	10.8	10.6	11.1	11.4	11.4	11.9	11.7	12.2	12.4	
	8H	11.4	11.9	11.7	12.2	12.5	12.6	13.1	12.9	13.4	13.7	
	12H	12.7	13.2	13.1	13.5	13.8	14.0	14.5	14.4	14.8	15.1	
4H	2H	4.4	5.0	4.7	5.3	5.5	4.8	5.4	5.1	5.6	5.9	
	3H	7.8	8.3	8.2	8.6	8.9	8.5	9.0	8.8	9.3	9.6	
	4H	9.8	10.2	10.2	10.6	10.9	10.6	11.0	10.9	11.3	11.7	
	6H	12.0	12.4	12.4	12.7	13.1	13.0	13.3	13.4	13.7	14.0	
	8H	13.2	13.5	13.6	13.9	14.3	14.3	14.6	14.7	15.0	15.4	
	12H	14.6	14.9	15.1	15.3	15.7	15.8	16.1	16.2	16.5	16.9	
8H	4H	10.8	11.1	11.2	11.4	11.8	11.3	11.6	11.7	12.0	12.4	
	6H	13.1	13.4	13.6	13.8	14.2	13.9	14.1	14.4	14.6	15.0	
	8H	14.5	14.7	15.0	15.2	15.6	15.4	15.6	15.9	16.1	16.5	
	12H	16.1	16.3	16.6	16.8	17.3	17.2	17.3	17.7	17.8	18.3	
12H	4H	11.0	11.3	11.4	11.7	12.1	11.5	11.8	11.9	12.2	12.6	
	6H	13.5	13.7	14.0	14.1	14.6	14.2	14.4	14.6	14.8	15.3	
	8H	15.0	15.2	15.5	15.6	16.1	15.8	16.0	16.3	16.4	16.9	
Variation of the observer position for the luminaire distances S												
S = 1.0H S = 1.5H S = 2.0H		+0.2 / -0.1 +0.3 / -0.3 +0.5 / -0.5					+0.2 / -0.1 +0.3 / -0.3 +0.5 / -0.5					
Standard table		---					---					
Correction		---					---					
Summand		---					---					
Corrected Glare Indices referring to 2300lm Total Luminous Flux												