
BLACK FOSTER



	٢		٢	۲
V	V	V	V	

וח	MF	:NC	:IO	NS	
	1.15			110	



Reference
Color
Category
Туре
Gross luminous flux
Color temperature
Chromatic stability
Color Rendering Index
Power

Lighting	efficiency
Delivered lum	inous flux
Light b	eam angle

Driver
Power values of the system
Frequency
Dimming

IC Rated
Environmental location
Recess measurements
Weight
Packaged weight
Packaging dimensions
Materials

PRODUCT	
BLACK FOSTER ASYM TRI 5 UL 3000K N	
U3734011N	
Matt black	
CEILING RECESSED	

LIGHT SOURCE

Name

Current

LED lifespan

LED
Depending on Mounting Accessories Lm
3000 K
MacAdam Step 3
CRI>90
Depending on Mounting Accessories W
Depending on Mounting Accessories mA
L90B10>102.000h

LIGHTING FIXTURE | PHOTOMETRIC DATA

90%	
0 Lm	
38°	

LIGHTING FIXTURE | ELECTRICAL DATA

Requires remote driver	
W	
Depending on Mounting Accessories	
Depending on Mounting Accessories	

OTHER DATA

5	
MP	
7 x 8.75 50 x 222	
1 lb 414 gr	
7 lb 529 gr	
61x6.10x2.87 in 295x155x73 mm	
ımınıum - Acrylonitrile Butadiene Styrene - Polycarbona	nte



AWARDS



Black Foster is our lineal recessed luminaire with "The invisible black" effect, also available in a trimless version. Hiding the source of light, Black Foster stands out for its visual comfort and its elegance.

