




DIMENSIONS



AWARDS



Name	BLACK FOSTER TRI 15 UL SPOT 3500K NMG
Reference	U3186113NMG
Color	Matt black-Metallized gold
Category	CEILING RECESSED

PRODUCT

Type	LED
Gross luminous flux	Depending on Mounting Accessories Lm
Color temperature	3500 K
Chromatic stability	MacAdam Step 3
Color Rendering Index	CRI>90
Power	Depending on Mounting Accessories W
Current	Depending on Mounting Accessories mA
LED lifespan	L90B10>102.000h

LIGHT SOURCE

Lighting efficiency	90%
Delivered luminous flux	0 Lm
Light beam angle	19°

LIGHTING FIXTURE | PHOTOMETRIC DATA

Driver	Requires remote driver
Power values of the system	W
Frequency	Depending on Mounting Accessories
Dimming	Depending on Mounting Accessories

LIGHTING FIXTURE | ELECTRICAL DATA


IC Rated	Yes
Environmental location	DAMP
Recess measurements	1.97 x 25.67 50 x 652
Weight	2.23 lb 1014 gr
Packaged weight	3.30 lb 1484 gr
Packaging dimensions	Ø4.13x42.52 in Ø105x1080 mm
Materials	Aluminium - Acrylonitrile Butadiene Styrene - Polycarbonate

OTHER DATA




Black Foster is our lineal recessed luminaire with "The invisible black" effect, also available in a trimless version. Hiding the source of light, Black Foster stands out for its visual comfort and its elegance.

POLAR DIAGRAM



CONICAL DIAGRAM



UGR

Glare Evaluation According to UGR												
p Ceiling	70	70	50	50	30	70	70	50	50	30	70	70
p Walls	50	30	50	30	30	50	30	50	30	30	50	30
p Floor	20	20	20	20	20	20	20	20	20	20	20	20
Room Size X Y	Viewing direction at right angles to lamp axis					Viewing direction parallel to lamp axis						
2H	2H	3.1	3.8	3.4	4.0	4.2	3.7	4.3	3.9	4.5	4.7	4.7
	3H	6.3	6.9	6.6	7.2	7.4	7.1	7.7	7.4	8.0	8.2	8.2
	4H	8.2	8.8	8.5	9.0	9.3	9.1	9.7	9.4	9.9	10.2	10.2
	6H	10.2	10.8	10.6	11.1	11.3	11.3	11.9	11.7	12.1	12.4	12.4
	8H	11.3	11.9	11.7	12.1	12.4	12.6	13.1	12.9	13.4	13.7	13.7
4H	12H	12.7	13.2	13.1	13.5	13.8	14.0	14.5	14.3	14.8	15.1	15.1
	2H	4.4	5.0	4.7	5.2	5.5	4.8	5.3	5.1	5.6	5.8	5.8
	3H	7.8	8.3	8.2	8.6	8.9	8.5	8.9	8.8	9.2	9.6	9.6
	4H	9.8	10.2	10.2	10.6	10.9	10.5	11.0	10.9	11.3	11.6	11.6
	6H	12.0	12.3	12.4	12.7	13.1	12.9	13.3	13.3	13.6	14.0	14.0
8H	8H	13.2	13.5	13.6	13.9	14.3	14.3	14.6	14.7	14.9	15.3	15.3
	12H	14.6	14.9	15.1	15.3	15.7	15.8	16.1	16.2	16.5	16.9	16.9
	4H	10.7	11.0	11.1	11.4	11.8	11.3	11.6	11.7	12.0	12.4	12.4
	6H	13.1	13.3	13.5	13.8	14.2	13.9	14.1	14.3	14.5	15.0	15.0
	8H	14.5	14.7	15.0	15.1	15.6	15.4	15.6	15.9	16.0	16.5	16.5
12H	12H	16.1	16.3	16.6	16.7	17.2	17.1	17.3	17.6	17.8	18.3	18.3
	4H	11.0	11.3	11.4	11.7	12.1	11.5	11.7	11.9	12.1	12.6	12.6
	6H	13.5	13.7	13.9	14.1	14.6	14.2	14.4	14.6	14.8	15.3	15.3
8H	15.0	15.1	15.5	15.6	16.1	15.8	15.9	16.3	16.4	16.9	16.9	
Variation of the observer position for the luminaire distances S												
S = 1.0H	+0.2 / -0.1					+0.2 / -0.1						
S = 1.5H	+0.3 / -0.3					+0.3 / -0.3						
S = 2.0H	+0.5 / -0.5					+0.5 / -0.5						
Standard table	---					---						
Correction Summand	---					---						
Corrected Glare Indices referring to 3450lm Total Luminous Flux												

GUÍA DE INSTALACIÓN



<https://youtu.be/SVWNEfbfVY>