




DIMENSIONS



۸	١	Α	i.	۸	D	n	c





PRODUCT

BLACK FOSTER SUSP 1600 UL SPOT DIM ON BOARD 2700K NTMG U3212150NTMG

Textured black-Metallized gold

LIGHT SOURCE

MacAdam Step 3

SUSPENSION

Type LED

Gross luminous flux

Name Reference

Color

Category

Color temperature

Chromatic stability

Color Rendering Index

Power

Current

Efficacy LED lifespan CRI>90 31.5 W

2850 Lm 2700 K

700 mA 90 Lm/W

L80B10 >60.000h

LIGHTING FIXTURE | PHOTOMETRIC DATA

Lighting efficiency

Delivered luminous flux

Light beam angle

90%

2565 Lm 19°

LIGHTING FIXTURE | ELECTRICAL DATA

Driver

Power values of the system

Frequency

Dimming

Included: ERP-PSB series or similar

37,00 W

50/60 Hz

DIM on Board

OTHER DATA

Environmental location

Junction box cover

Junction box cover color

Junction box cover measurements

Cord Length

Fast adjustment tensioner

Weight

Packaged weight

Packaging dimensions

Materials

DAMP

Included. For octogonal Junction box

Textured white. Other finishing, please consult

Ø5.51 in | Ø140 mm

Yes

9.42 lb | 4275 gr

I MAX. 3.05 m

13.01 lb | 5900 gr

Ø6.10x68.31 in | Ø155x1735 mm

Aluminium - Acrylonitrile Butadiene Styrene - Polycarbonate




Black Foster Suspension is the product that transfers the claimed effect "The Invisible Black" to a linear suspended system. It is composed by a series of modules which combine light emisions with dark segments. Nevertheless, wether If It is On or Off, Black Foster always preserves the aesthetic of a perfect dark line.






POLAR DIAGRAM



CONICAL DIAGRAM



UGR

Glare E	valuat										
ρ Ceiling		70	70	50	50	30	70	70	50	50	30
ρ Walls		50	30	50	30	30	50	30	50	30	30
ρ Floor		20	20	20	20	20	20	20	20	20	20
Room Size X Y		Viewing direction at right angles to lamp axis				Viewing direction parallel to lamp axis					
2H	2H 3H 4H 6H 8H 12H	-1.8 1.7 3.7 5.9 7.1 8.4	-1.1 2.3 4.3 6.5 7.6 8.9	-1.5 2.0 4.0 6.2 7.4 8.8	-0.9 2.6 4.5 6.7 7.9 9.2	-0.7 2.8 4.8 7.0 8.2 9.5	-0.9 3.0 4.8 7.1 8.3 9.7	-0.3 3.6 5.4 7.6 8.8 10.2	-0.7 3.2 5.1 7.4 8.7 10.1	-0.1 3.8 5.6 7.9 9.1 10.5	0.1 4.0 5.9 8.2 9.4 10.8
4H	2H 3H 4H 6H 8H 12H	-0.4 3.3 5.4 7.7 8.9 10.4	0.2 3.8 5.8 8.0 9.2 10.6	-0.1 3.7 5.8 8.1 9.3 10.8	0.4 4.1 6.1 8.4 9.6 11.0	0.7 4.4 6.5 8.8 10.0 11.5	0.1 4.2 6.2 8.6 10.0	0.7 4.7 6.6 9.0 10.3 11.8	0.4 4.5 6.6 9.0 10.4 11.9	1.0 5.0 7.0 9.3 10.7 12.2	1.2 5.3 7.3 9.7 11.1 12.6
8H	4H 6H 8H 12H	6.4 8.8 10.2 11.9	6.7 9.1 10.4 12.0	6.8 9.3 10.7 12.4	7.1 9.5 10.9 12.5	7.5 9.9 11.3 13.0	7.0 9.6 11.1 12.9	7.3 9.8 11.3 13.0	7.4 10.0 11.6 13.4	7.7 10.2 11.8 13.5	8.1 10.7 12.2 14.0
12H	4H 6H 8H	6.6 9.2 10.7	6.9 9.4 10.9	7.1 9.7 11.2	7.3 9.8 11.4	7.7 10.3 11.8	7.2 9.9 11.5	7.4 10.1 11.7	7.6 10.3 12.0	7.8 10.5 12.1	8.3 11.0 12.6
Variation of t	he observe	r position	for the lun	ninaire dist	ances S						
S = 1.0H S = 1.5H S = 2.0H		+0.2 / -0.1 +0.3 / -0.3 +0.5 / -0.5				+0.2 / -0.1 +0.3 / -0.3 +0.5 / -0.5					
Standard Correc Summ	tion										
Corrected Gla	are Indices	referring t	o 2850lm	Total Lumi	nous Flux						

