




DIMENSIONS



ACCESSORIES



BLACK FOSTER CUSTOM
ACCESSORIES

PRODUCT

Name	BLACK FOSTER CUSTOM MODULE 5 UL SPOT DIM 0/10V 3500K NMG
Reference	U4534113NMG
Color	Black-Metallized gold
Category	CUSTOM SYSTEMS

LIGHT SOURCE

Type	LED
Gross luminous flux	1150 Lm
Color temperature	3500 K
Chromatic stability	MacAdam Step 3
Color Rendering Index	CRI>90
Power	10.5 W
Efficacy	109 Lm/W
LED lifespan	L80B10 >60.000h

LIGHTING FIXTURE | PHOTOMETRIC DATA

Lighting efficiency	90%
Delivered luminous flux	1035 Lm
Light beam angle	19°

LIGHTING FIXTURE | ELECTRICAL DATA

Power values of the system	12,50 W
Dimming	0-10V


OTHER DATA

Environmental location	DAMP
Track type	Black Foster Custom Surface Track
Weight	0.36 lb 165 gr
Packaged weight	0.51 lb 232 gr
Packaging dimensions	9.72x4.41x1.89 in 247x112x48 mm
Materials	Aluminium / Acrylonitrile Butadiene Styrene / Polycarbonate




Black Foster is the lighting fixture that transfers the applauded "Invisible Black" effect to a linear system. Black Foster is composed of a series of combinable modules enabling the alternation of segments with light emission and without light emission. However, whether it is ON or OFF, this luminaire always keeps the aesthetics of a perfect dark line. To the observer, it is impossible to distinguish between Black Foster parts that emit light from those that don't. Black Foster's modularity provides a wide range of different combinations, allowing to set up the light emission location as many times as needed, and adapting itself to the requirements of each project in particular.

POLAR DIAGRAM




CONICAL DIAGRAM



UGR

Glare Evaluation According to UGR											
ρ Ceiling		70	70	50	50	30	70	70	50	50	30
ρ Walls		50	30	50	30	30	50	30	50	30	30
ρ Floor		20	20	20	20	20	20	20	20	20	20
Room Size X Y		Viewing direction at right angles to lamp axis					Viewing direction parallel to lamp axis				
2H	2H	3.2	3.9	3.5	4.1	4.3	3.8	4.4	4.0	4.6	4.8
	3H	6.4	7.0	6.7	7.3	7.5	7.2	7.8	7.5	8.1	8.3
	4H	8.3	8.9	8.6	9.1	9.4	9.2	9.8	9.5	10.0	10.3
	6H	10.3	10.9	10.7	11.2	11.4	11.4	12.0	11.8	12.2	12.5
	8H	11.4	12.0	11.8	12.2	12.5	12.7	13.2	13.0	13.5	13.8
	12H	12.8	13.3	13.2	13.6	13.9	14.1	14.6	14.4	14.9	15.2
4H	2H	4.5	5.1	4.8	5.3	5.6	4.9	5.4	5.2	5.7	5.9
	3H	7.9	8.4	8.3	8.7	9.0	8.6	9.0	8.9	9.3	9.7
	4H	9.9	10.3	10.3	10.7	11.0	10.6	11.1	11.0	11.4	11.7
	6H	12.1	12.4	12.5	12.8	13.2	13.0	13.4	13.4	13.7	14.1
	8H	13.3	13.6	13.7	14.0	14.4	14.4	14.7	14.8	15.0	15.4
	12H	14.7	15.0	15.2	15.4	15.8	15.9	16.2	16.3	16.6	17.0
8H	4H	10.8	11.1	11.2	11.5	11.9	11.4	11.7	11.8	12.1	12.5
	6H	13.2	13.4	13.6	13.9	14.3	14.0	14.2	14.4	14.6	15.1
	8H	14.6	14.8	15.1	15.2	15.7	15.5	15.7	16.0	16.1	16.6
	12H	16.2	16.4	16.7	16.8	17.3	17.2	17.4	17.7	17.9	18.4
12H	4H	11.1	11.4	11.5	11.8	12.2	11.6	11.8	12.0	12.2	12.7
	6H	13.6	13.8	14.0	14.2	14.7	14.3	14.5	14.7	14.9	15.4
	8H	15.1	15.2	15.6	15.7	16.2	15.9	16.0	16.4	16.5	17.0
Variation of the observer position for the luminaire distances S											
S = 1.0H		+0.2 / -0.1					+0.2 / -0.1				
S = 1.5H		+0.3 / -0.3					+0.3 / -0.3				
S = 2.0H		+0.5 / -0.5					+0.5 / -0.5				
Standard table		---					---				
Correction		---					---				
Summand		---					---				
Corrected Glare Indices referring to 1150lm Total Luminous Flux											


BLACK FOSTER CUSTOM UL



BLACK FOSTER CUSTOM SURFACE	3.28ft (1m) UL	U452-01-00-	NT	WT
BLACK FOSTER CUSTOM SURFACE	6.56ft (2m) UL	U452-02-00-	NT	WT


BLACK FOSTER CUSTOM COVER	Gap 250 UL	U452-00-01-	N	9.84 in / 250 mm
BLACK FOSTER CUSTOM COVER	Gap 500 UL	U452-00-02-	N	16.69 in / 500 mm

L




BLACK FOSTER CUSTOM SURFACE	L-Joint UL	U452-04-00-	NT	WT
BLACK FOSTER CUSTOM SURFACE	T-Joint UL	U452-05-00-	NT	WT
BLACK FOSTER CUSTOM SURFACE	X-Joint UL	U452-06-00-	NT	WT

BLACK FOSTER CUSTOM SURFACE
L-Joint UL




Electrical connection not included

BLACK FOSTER CUSTOM SURFACE
T-Joint UL



Electrical connection not included

BLACK FOSTER CUSTOM SURFACE
X-Joint UL





Electrical connection not included

		P	V	D
CONSTANT VOLTAGE	U100-00-78	96 W	48 V	8.16 x 2.97 x 1.30 in
LED POWER SUPPLY				207 x 75.4 x 33 mm

120 & 277V | 50/60 Hz

UL DROP
VOLTAGE TABLE

		CABLE LENGTH			
		16.40ft 5m	32.80ft 10m	65.62ft 20m	98.43ft 30m
POWER	CABLE SECTION	TRACK LENGTH			
96 W	AWG16	164ft 50m	164ft 50m	131.32ft 40m	82ft 25m



COLOUR | N ■ | NT ■ | WT □ |

BLACK FOSTER CUSTOM UL


BLACK FOSTER CUSTOM TRACK COMPONENTS



BLACK FOSTER CUSTOM SURFACE			
End UL	U452-00-03-	N	W
Cover thickness = 0.12in (3mm)			




BLACK FOSTER CUSTOM SURFACE			
End Feed UL	U452-00-04-	N	W
Cover thickness = 0.12in (3mm)			




BLACK FOSTER CUSTOM SURFACE	
Straight Joiner UL	U452-00-05


CONNECTION COMPONENTS




Live-End Connector 48V UL
U338-00-01- N




L-Joint Connector 48V UL
U338-00-12- N



Central Connector 48V UL
U338-00-02- N



T-Joint Connector 48V UL
U450-00-07- N



X-Joint Connector 48V UL
U450-00-08- N

SUSPENSION COMPONENTS



Black Foster Suspension Kit (2 Units) UL			
U450-00-09-	NT	WT	
Suggested Mounting accessories quantities			
3.28ft (1000mm)	-	2 Pcs.	
6.56ft (2000mm)	-	3 Pcs.	



Suspension Feed Kit 48V UL
U338-00-17- N W
 DIM

*For remote power supply