iO SURFACE



	Name	IO SURFACE UL 20º 2700K WT
	Reference	U2630110WT
	Color	Textured white
	Category	SURFACE
	Туре	LED
	Gross luminous flux	Depending on Mounting Accessories Lm
	Color temperature	2700 K
	Chromatic stability	MacAdam Step 2
	Color Rendering Index	CRI>90
	Power	Depending on Mounting Accessories W
DIMENSIONS	LED lifespan	Depending on Mounting Accessories mA
		LIGHTING FIXTURE PHOTOMETRIC DATA
2.75in (70mm)	Lighting efficiency	92%
	Delivered luminous flux	0 Lm
	Light beam angle	20°
1.42in Ø1.57in		
(36mm) (40mm)		LIGHTING FIXTURE ELECTRICAL DATA
3.30in (84mm)	Driver	Requires remote driver
••		W
	Power values of the system	VV
	Power values of the system Frequency	VV Depending on Mounting Accessories
ACCESORIES	Frequency	Depending on Mounting Accessories
	Frequency	Depending on Mounting Accessories
	Frequency	Depending on Mounting Accessories Depending on Mounting Accessories
ER DIFFUSER ANTI-GLARE HONEYCOMB	Frequency Dimming	Depending on Mounting Accessories Depending on Mounting Accessories OTHER DATA
	Frequency Dimming Environmental location	Depending on Mounting Accessories Depending on Mounting Accessories OTHER DATA DAMP
XER DIFFUSER ANTI-GLARE HONEYCOMB	Frequency Dimming Environmental location Junction box cover	Depending on Mounting Accessories Depending on Mounting Accessories OTHER DATA DAMP Included. For octogonal Junction box
C C C C C C C C C C C C C C C C C C C	Frequency Dimming Environmental location Junction box cover Junction box cover color	Depending on Mounting Accessories Depending on Mounting Accessories OTHER DATA DAMP Included. For octogonal Junction box Textured white. Other finishing, please consult
ER DIFFUSER ANTI-GLARE HONEYCOMB	Frequency Dimming Environmental location Junction box cover Junction box cover color Junction box cover measurements	Depending on Mounting Accessories Depending on Mounting Accessories OTHER DATA DAMP Included. For octogonal Junction box Textured white. Other finishing, please consult Ø5.51 in Ø140 mm
R DIFFUSER ANTI-GLARE HONEYCOMB	Frequency Dimming Environmental location Junction box cover Junction box cover color Junction box cover measurements Swivel angle	Depending on Mounting Accessories Depending on Mounting Accessories OTHER DATA DAMP Included. For octogonal Junction box Textured white. Other finishing, please consult Ø5.51 in Ø140 mm 325°
ER DIFFUSER ANTI-GLARE HONEYCOMB	Frequency Dimming Environmental location Junction box cover Junction box cover color Junction box cover measurements Swivel angle Rotation angle	Depending on Mounting Accessories Depending on Mounting Accessories OTHER DATA DAMP Included. For octogonal Junction box Textured white. Other finishing, please consult Ø5.51 in Ø140 mm 325° 355°
ER DIFFUSER ANTI-GLARE HONEYCOMB	Frequency Dimming Environmental location Junction box cover Junction box cover color Junction box cover measurements Swivel angle Rotation angle Weight	Depending on Mounting Accessories Depending on Mounting Accessories OTHER DATA DAMP Included. For octogonal Junction box Textured white. Other finishing, please consult Ø5.51 in Ø140 mm 325° 355° 0.76 lb 343 gr
ER DIFFUSER ANTI-GLARE HONEYCOMB	Frequency Dimming Environmental location Junction box cover Junction box cover color Junction box cover measurements Swivel angle Rotation angle Weight Packaged weight	Depending on Mounting Accessories Depending on Mounting Accessories OTHER DATA DAMP Included. For octogonal Junction box Textured white. Other finishing, please consult Ø5.51 in Ø140 mm 325° 355° 0.76 lb 343 gr 0.93 lb 423 gr

IO is a LED spotlight miniaturised in a fixture that is so small that it fits on the palm of your hand. Designed for accent lighting applications, its small dimensions mean it can be fitted in display cabinets, shop windows and small places without generating an invasive presence on the scene.

JOKERLIGHT LLC 333 SE 2nd Av, Suite 2000 · Miami, FL 33131 (USA) info@jokerlight.com · jokerlight.com

PREMIO ADCV 2017 ORO 19-08-25 / 14:43







PRODUCT

Model
Reference
Category


PRODUCT
Beam Mixer Diffuser
0805-01-00
Accessories
NOT SOLD SEPARATELY AFFECTS THE LIGHTING PARAMETERS

The Beam Mixer Diffuser is used to smooth beam artifacts caused by parabolic, Fresnel, or TIR lens collimators without significant broadening.

The unique mixing design provides superior far-field smoothing and color mixing with high on-axis brightness. Compared with traditional diffusers, it maintains higher central beam candlepower (CBCP), and produce less undesirable "field light" at higher angles.







PRODUCT

Model
Reference
Colour
Category

PRODUCT	
Anti-glare Honeycomb Louver	
0806-00-00 WT NT	
WT □ Textured white NT ■ Textured black	
Accessories	
NOT SOLD SEPARATELY	A
AFFECTS THE LIGHTING PARAMETERS	\odot

Accessory made up of louver in the shape of a honeycomb panel to reduce glare and the effects of direct rays of vision.

