




## DIMENSIONS



Name	BLACK FOSTER TRI 5 UL FLOOD 3500K N
Reference	U3184013N
Color	Matt black
Category	CEILING RECESSED

## PRODUCT

Type	LED
Gross luminous flux	Depending on Mounting Accessories Lm
Color temperature	3500 K
Chromatic stability	MacAdam Step 3
Color Rendering Index	CRI>90
Power	Depending on Mounting Accessories W
Current	Depending on Mounting Accessories mA
LED lifespan	L90B10>102.000h

## LIGHT SOURCE

## LIGHTING FIXTURE | PHOTOMETRIC DATA

Lighting efficiency	92%
Delivered luminous flux	0 Lm
Light beam angle	38°

## LIGHTING FIXTURE | ELECTRICAL DATA

Driver	Requires remote driver
Power values of the system	W
Frequency	Depending on Mounting Accessories
Dimming	Depending on Mounting Accessories

## OTHER DATA

IC Rated	Yes
Environmental location	DAMP
Recess measurements	1.97 x 8.75   50 x 222
Weight	0.78 lb   354 gr
Packaged weight	1.03 lb   469 gr
Packaging dimensions	11.61x6.10x2.87 in   295x155x73 mm
Materials	Aluminium - Acrylonitrile Butadiene Styrene - Polycarbonate




## AWARDS




Black Foster is our lineal recessed luminaire with "The invisible black" effect, also available in a trimless version. Hiding the source of light, Black Foster stands out for its visual comfort and its elegance.

POLAR DIAGRAM



CONICAL DIAGRAM



UGR

Glare Evaluation According to UGR												
p Ceiling		70	70	50	50	30	70	70	50	50	30	
p Walls		50	30	50	30	30	50	30	50	30	30	
p Floor		20	20	20	20	20	20	20	20	20	20	
Room Size X Y	Viewing direction at right angles to lamp axis					Viewing direction parallel to lamp axis						
2H	2H	-1.7	-1.0	-1.4	-0.8	-0.6	0.2	0.8	0.4	1.0	1.2	
	3H	-1.2	-0.6	-0.9	-0.4	-0.1	0.5	1.1	0.8	1.3	1.5	
	4H	-0.2	0.3	0.1	0.6	0.8	1.2	1.8	1.5	2.0	2.3	
	6H	1.7	2.2	2.0	2.5	2.8	2.7	3.2	3.0	3.5	3.7	
	8H	3.0	3.5	3.4	3.8	4.1	3.8	4.3	4.1	4.6	4.9	
12H	4.7	5.2	5.0	5.5	5.8	5.3	5.8	5.7	6.1	6.4		
4H	2H	-1.7	-1.1	-1.4	-0.9	-0.6	0.1	0.6	0.4	0.9	1.2	
	3H	-0.7	-0.3	-0.4	0.0	0.3	0.7	1.2	1.0	1.5	1.8	
	4H	0.7	1.1	1.1	1.5	1.8	1.9	2.3	2.3	2.6	3.0	
	6H	3.2	3.5	3.6	3.9	4.2	3.9	4.2	4.3	4.6	5.0	
	8H	4.7	5.0	5.2	5.4	5.8	5.3	5.6	5.7	6.0	6.4	
12H	6.6	6.8	7.0	7.2	7.7	7.1	7.3	7.5	7.7	8.1		
8H	4H	1.7	2.0	2.1	2.4	2.8	2.6	2.9	3.0	3.2	3.6	
	6H	4.5	4.7	5.0	5.2	5.6	5.0	5.2	5.5	5.7	6.1	
	8H	6.3	6.5	6.8	6.9	7.4	6.7	6.8	7.1	7.3	7.8	
	12H	8.3	8.5	8.8	8.9	9.4	8.7	8.8	9.2	9.3	9.8	
12H	4H	2.1	2.3	2.5	2.7	3.1	2.8	3.1	3.3	3.5	3.9	
	6H	5.1	5.2	5.5	5.7	6.1	5.5	5.6	5.9	6.1	6.6	
	8H	6.9	7.1	7.4	7.5	8.0	7.3	7.4	7.7	7.9	8.4	
Variation of the observer position for the luminaire distances S												
S = 1.0H	+0.9 / -0.3					+1.3 / -0.4						
S = 1.5H	+1.9 / -0.6					+2.7 / -0.7						
S = 2.0H	+3.1 / -0.8					+4.2 / -1.0						
Standard table	---					---						
Correction Summand	---					---						
Corrected Glare Indices referring to 1150lm Total Luminous Flux												

GUÍA DE INSTALACIÓN



<https://youtu.be/SVWNEfbfVY>