BLACK FOSTER





DIMENSIONS

3.82in (97mm) 1.73in (44mm)

 \bigcirc

0

0

9 D P

4IN. 1.97in (50mm)

5.12in (130mm)

.57in (40mm)

Туре
Gross luminous flux
Color temperature
Chromatic stability
Color Rendering Index
Power
Current
LED lifespan

Lighting efficiency
Delivered luminous flux
Light beam angle

Driver
Power values of the system
Frequency
Dimming

IC Rated
Environmental location
Recess measurements
Weight
Packaged weight
Packaging dimensions
Materials

BLACK F	OSTER TR	RI 3 UL F	FLOOI	D 4000)K NM	G	
U318301	2NMG						
Matt bla	ck-Metalli	zed gold	ł				
CEILING	RECESSE	D					

LIGHT SOURCE

LED
Depending on Mounting Accessories Lm
4000 K
MacAdam Step 3
CRI>90
Depending on Mounting Accessories W
Depending on Mounting Accessories mA
L90B10>102.000h

LIGHTING FIXTURE | PHOTOMETRIC DATA

92%	
0 Lm	
38°	

LIGHTING FIXTURE | ELECTRICAL DATA

Requires remote driver	
W	
Depending on Mounting Accessories	
Depending on Mounting Accessories	

OTHER DATA

Yes	
DAMP	
1.97 x 5.35 50 x 136	
0.48 lb 219 gr	
0.70 lb 314 gr	
8.35x6.10x2.87 in 212x155x73 mm	
Aluminium - Acrylonitrile Butadiene Styrene - Pol	ycarbonate



AWARDS



Black Foster is our lineal recessed luminaire with "The invisible black" effect, also available in a trimless version. Hiding the source of light, Black Foster stands out for its visual comfort and its elegance.

