




### DIMENSIONS



### ACCESSORIES



TRACK 48V OPTIONS

### AWARDS



Name	SIX M 48V UL DIM DALI 19° 3000K WTW
Reference	U3300211WTW
Color	Textured white - White track
Category	TRACKLIGHTS

Type	LED
Gross luminous flux	2130 Lm
Color temperature	3000 K
Chromatic stability	MacAdam Step 2
Color Rendering Index	CRI>90
Power	17 W
Efficacy	125 Lm/W
LED lifespan	L90B10>55.000h

Lighting efficiency	93%
Delivered luminous flux	1981 Lm
Light beam angle	19°

Power values of the system	18,00 W
Dimming	DALI

Environmental location	DAMP
Swivel angle	310°
Rotation angle	360°
Track type	Track 48V
Weight	0.67 lb   303 gr
Packaged weight	0.83 lb   375 gr
Packaging dimensions	7.40x6.50x2.09 in   188x165x53 mm
Materials	Aluminium - Polycarbonate

### PRODUCT

### LIGHT SOURCE

### LIGHTING FIXTURE | PHOTOMETRIC DATA


### LIGHTING FIXTURE | ELECTRICAL DATA

### OTHER DATA





Six 48V is a family of spotlights for low voltage tracklight applications that stands out for its lightness and elegance. Available in L, M, S, and XS, its body; disk looking, rounded shaped, encloses an innovative combination of reflector and lens. The combined action of both, allows Six to direct light rays with the maximum uniformity in a very small distance that, at the same time, has made possible its differential design-reduced and minimalist-. In addition, Six can be freely articulated due to its airy arm which allows the spotlight to be orientated in any direction.

POLAR DIAGRAM



CONICAL DIAGRAM






TRACK 48V TRIMLESS UL

TRACK 48V TRIMLESS 3.28ft (1m) UL	U338-01-00-	N	WT
TRACK 48V TRIMLESS 6.56ft (2m) UL	U338-02-00-	N	WT
TRACK 48V TRIMLESS Corner 90° One Plane UL	U338-06-00-	N	WT
TRACK 48V TRIMLESS Corner 90° Two Planes UL	U338-07-00-	N	WT


PLASTERBOARD CEILING MANDATORY THICKNESS 0.50in (12.5mm)  
RECOMMENDED FOR INSTALLATIONS WHERE THE PROFILE CAN BE INSTALLED BEFORE THE FALSE PLASTERBOARD CEILING

TRACK 48V TRIMLESS  
Corner 90° One Plane UL




\*Electrical connection not included

TRACK 48V TRIMLESS  
Corner 90° Two Planes UL



\*Electrical connection not included


TRIMLESS INSTALLATION GUIDE  
<https://youtu.be/SVWNEfblfVY>




TRACK 48V SURFACE UL

TRACK 48V SURFACE 3.28ft (1m) UL	U338-11-00-	NT	WT
TRACK 48V SURFACE 6.56ft (2m) UL	U338-12-00-	NT	WT
TRACK 48V SURFACE Corner 90° One Plane UL	U338-14-00-	NT	WT

TRACK 48V SURFACE  
Corner 90° One Plane UL




\*Electrical connection not included




TRACK 48V SURFACE SHORT UL

TRACK 48V SURFACE SHORT 3.28ft (1m) UL	U338-21-00-	NT	WT
TRACK 48V SURFACE SHORT 6.56ft (2m) UL	U338-22-00-	NT	WT
TRACK 48V SURFACE SHORT Corner 90° One Plane UL	U338-24-00-	NT	WT

TRACK 48V SURFACE SHORT  
Corner 90° One Plane UL



\*Electrical connection not included




	P	V	D
<b>CONSTANT VOLTAGE LED POWER SUPPLY</b>	<b>U100-00-78</b>	96W	48V
			8.16 x 2.97 x 1.30 in 207 x 75.4 x 33 mm

120 & 277 V | 50/60 Hz


UL DROP VOLTAGE TABLE

POWER	CABLE SECTION	CABLE LENGTH			
		16.40ft 5m	32.80ft 10m	65.62ft 20m	98.43ft 30m
96W	AWG 16	164ft	164ft	131.32ft	82ft
		50m	50m	40m	25m


ALL 48V TRACK UL



Live-End Connector 48V UL  
U338-00-01- | N | W |




L-JOINT Connector 48V UL  
U338-00-12- | N | W |




Corner 90° Connector One Plane 48V UL  
U338-00-24- | N | W |

\*Not suitable for trimless version



Central Connector 48V UL  
U338-00-02- | N | W |



Wireless Control 48V UL  
U434-01-31- | N | W |  
Casambi/AAG Stucchi App



Cover Gap 3,28 ft (1m) 48V UL  
U338-00-30- | N |


TRIMLESS 48V UL



Trimless T-Bracket 48V UL  
U338-00-03



Clamp for M6 ROD UL  
U338-00-09  
\*See accessories quantities




Trimless Long T-Bracket 48V UL  
U338-00-04



Track Clamp UL  
U338-00-10  
\*See accessories quantities



Trimless Straight Joiners 48V (2 units) UL  
U338-00-05- | N | WT |



Suspension Kit UL  
U338-00-08  
\*See accessories quantities




Trimless Plaster Installation Guard  
3.28ft (1m) 48V UL  
U338-00-21

\* SUGGESTED MOUNTING ACCESSORIES QUANTITIES

- 3.28ft (1000mm) - 2 Pcs.
- 6.56ft (2000mm) - 3 Pcs.
- 9.84ft (3000mm) - 4 Pcs.

SURFACE, SUSPENSION , SURFACE SHORT & SUSPENSION SHORT 48V UL



Surface Straight Joiner 48V UL  
U338-00-11

TRIMLESS, SURFACE & SUSPENSION 48V UL



End 48V UL

U338-00-06- | NT | WT |



End feed 48V UL

U338-00-07- | NT | WT |

SURFACE SHORT & SUSPENSION SHORT 48V UL



Short End 48V UL

U338-00-18- | NT | WT |



Short End feed 48V UL

U338-00-19- | NT | WT |

SUSPENSION & SUSPENSION SHORT 48V UL



Suspension Kit 48V [2 units] UL

U338-00-15- | NT | WT |



Suspension feed Kit 48V UL

U338-00-17- | N | W |



\*For remote power supply