iO SURFACE



	Name IO SURFACE UL 56º 3000K WT
	Reference U2630131WT
	Color Textured white
	Category SURFACE
and the second sec	
	Type LED
	Depending on Mounting Accessories Lm
	or temperature 3000 K
	matic stability MacAdam Step 2
Color F	endering Index CRI>90
	Power Depending on Mounting Accessories W
DIMENSIONS	Current Depending on Mounting Accessories mA
	LED lifespan L90B10>55.000h
	LIGHTING FIXTURE PHOTOMETRIC DA
E Lig	hting efficiency 86%
	l luminous flux 0 Lm
II Delivere	
الله الله الله الله الله الله الله الله	ht beam angle 56°
Ø1.42in Ø1.57in	
Ø1.42in Ø1.57in (36mm) (40mm) 3.30in (84mm)	ht beam angle 56°
01.42in 01.57in (36mm) (40mm) 3.30in (84mm)	beam angle 56° LIGHTING FIXTURE ELECTRICAL DAT/ Driver Requires remote driver
Ø1.42in Ø1.57in (36mm) (40mm) 3.30in (84mm)	beam angle 56° LIGHTING FIXTURE ELECTRICAL DAT/ Driver Requires remote driver s of the system W
21.42in Ø1.57in 36mm) (40mm) 3.30in (84mm) Power value	Initial beam angle 56° LIGHTING FIXTURE ELECTRICAL DATA Driver Requires remote driver s of the system W Frequency Depending on Mounting Accessories
11.42in Ø1.57in 36mm) (40mm) 3.30in (84mm) Power value	Initial beam angle 56° LIGHTING FIXTURE ELECTRICAL DATA Driver Requires remote driver s of the system W Frequency Depending on Mounting Accessories
21.42in Ø1.57in 36mm) (40mm) 3.30in (84mm) Power value ACCESORIES Environ	Initial beam angle 56° Driver LIGHTING FIXTURE ELECTRICAL DAT/ Driver Requires remote driver s of the system W Frequency Depending on Mounting Accessories Dimming Depending on Mounting Accessories
1.42in Ø1.57in 86mm) (40mm) 3.30in (84mm) Power value ACCESORIES Environ	Initial priver 56° Driver Requires remote driver s of the system W Frequency Depending on Mounting Accessories Dimming OTHER DATA
01.42in 01.57in 34mm) (40mm) 3.30in (84mm) Power value Power value Power value Environ Environ LOUVER	Initial priver 56° Driver Requires remote driver s of the system W Frequency Depending on Mounting Accessories Dimming Depending on Mounting Accessories OTHER DATA DAMP
01.42in 01.57in 34mm) (40mm) 3.30in (84mm) Power value Power value Power value Environ Environ LOUVER	Initial priver 56° Driver Requires remote driver s of the system W Frequency Depending on Mounting Accessories Dimming Depending on Mounting Accessories OTHER DATA DAMP Included. For octogonal Junction box Textured white. Other finishing, please consult
1.42in Ø1.57in 6mm) (40mm) 3.30in (84mm) Power value ACCESORIES ACCESORIES Environ COUFFUSER ANTI-GLARE HONEYCOMB LOUVER Junction	Initial priver 56° Driver Requires remote driver s of the system W Frequency Depending on Mounting Accessories Dimming Depending on Mounting Accessories OTHER DATA DAMP Included. For octogonal Junction box Textured white. Other finishing, please consultation
1.42in Ø1.57in 6mm) (40mm) 3.30in (84mm) Power value ACCESORIES Comparison R DIFFUSER ANTI-GLARE HONEYCOMB LOUVER Junction	Init beam angle 56° Init beam angle 56° Init beam angle LIGHTING FIXTURE ELECTRICAL DAT/ Driver Requires remote driver s of the system W Frequency Depending on Mounting Accessories Dimming Depending on Mounting Accessories OTHER DATA DAMP Included. For octogonal Junction box Textured white. Other finishing, please consumeasurements Ø5.51 in Ø140 mm Ø5.51 in Ø140 mm
1.42in Ø1.57in (40mm) 3.30in (84mm) Power value Power value Power value Environ Environ LOUVER	bit beam angle 56° Driver Requires remote driver s of the system W Frequency Depending on Mounting Accessories Dimming Depending on Mounting Accessories OTHER DATA DAMP Included. For octogonal Junction box Textured white. Other finishing, please consumations passurements 95.51 in Ø140 mm Swivel angle 325°
21.42in Ø1.57in 36mm) (40mm) 3.30in (84mm) Power value ACCESORIES	Initial priver 56° Driver Requires remote driver s of the system W Frequency Depending on Mounting Accessories Dimming Depending on Mounting Accessories OTHER DATA DAMP Included. For octogonal Junction box Textured white. Other finishing, please consumeasurements Swivel angle 325° Rotation angle 355°
Ø1.42in Ø1.57in (36mm) (40mm) 3.30in (84mm) Power value ACCESORIES ACCESORIES Environ XER DIFFUSER ANTI-GLARE HONEYCOMB LOUVER Junction Junction box cover 	Init beam angle 56° Init beam angle 56° Init beam angle LIGHTING FIXTURE ELECTRICAL DAT/ Driver Requires remote driver s of the system W Frequency Depending on Mounting Accessories Dimming Depending on Mounting Accessories OTHER DATA DAMP Included. For octogonal Junction box Textured white. Other finishing, please consumers Swivel angle 325° Rotation angle 355° Weight 0.76 lb 343 gr

IO is a LED spotlight miniaturised in a fixture that is so small that it fits on the palm of your hand. Designed for accent lighting applications, its small dimensions mean it can be fitted in display cabinets, shop windows and small places without generating an invasive presence on the scene.

JOKERLIGHT LLC 333 SE 2nd Av, Suite 2000 · Miami, FL 33131 (USA) info@jokerlight.com · jokerlight.com

PREMIO ADCV 2017 ORO 19-08-25 / 14:38







PRODUCT

Model
Reference
Category


PRODUCT
Beam Mixer Diffuser
0805-01-00
Accessories
NOT SOLD SEPARATELY AFFECTS THE LIGHTING PARAMETERS

The Beam Mixer Diffuser is used to smooth beam artifacts caused by parabolic, Fresnel, or TIR lens collimators without significant broadening.

The unique mixing design provides superior far-field smoothing and color mixing with high on-axis brightness. Compared with traditional diffusers, it maintains higher central beam candlepower (CBCP), and produce less undesirable "field light" at higher angles.







PRODUCT

Model
Reference
Colour
Category

PRODUCT	
Anti-glare Honeycomb Louver	
0806-00-00 WT NT	
WT □ Textured white NT ■ Textured black	
Accessories	
NOT SOLD SEPARATELY	A
AFFECTS THE LIGHTING PARAMETERS	٢

Accessory made up of louver in the shape of a honeycomb panel to reduce glare and the effects of direct rays of vision.

