
# BLACK FOSTER



۲	۲	۲	۲	۲
V	V	V	V	V

IONS	(	I	S	N	ľ	E	1	N	l	D
------	---	---	---	---	---	---	---	---	---	---



Name
Reference
Color
Category
Туре
Gross luminous flux
Color temperature

Color temperature
Chromatic stability
Color Rendering Index
Power
Current
LED lifespan

Lighting efficiency
Delivered luminous flux
Light beam angle

Driver
Power values of the system
Frequency
Dimming

IC Rated
Environmental location
Recess measurements
Weight
Packaged weight
Packaging dimensions
Materials

PRODUCT	
BLACK FOSTER ASYM TRI 5 UL 3500K N	
U3734013N	
Matt black	
CEILING RECESSED	

## LIGHT SOURCE

LED
Depending on Mounting Accessories Lm
3500 K
MacAdam Step 3
CRI>90
Depending on Mounting Accessories W
Depending on Mounting Accessories mA
L90B10>102.000h

#### LIGHTING FIXTURE | PHOTOMETRIC DATA

90%	
0 Lm	
38°	

## LIGHTING FIXTURE | ELECTRICAL DATA

Requires remote driver	
W	
Depending on Mounting Accessories	
Depending on Mounting Accessories	

### OTHER DATA

DAMP	
1.97 x 8.75   50 x 222	
0.91 lb   414 gr	
1.17 lb   529 gr	
11.61x6.10x2.87 in   295	x155x73 mm
Aluminium - Acrylonitr	le Butadiene Styrene - Polycarbon



AWARDS





Black Foster is our lineal recessed luminaire with "The invisible black" effect, also available in a trimless version. Hiding the source of light, Black Foster stands out for its visual comfort and its elegance.





### POLAR DIAGRAM





GUÍA DE INSTALACIÓN



https://jourd.bc/ottriteIbitti

