## iO SURFACE



Name	IO SURFACE UL 20º 4000K NT 
Color	Textured black
	SURFACE
Category	SURFACE
A CONTRACT OF CONTRACT.	
	LIGHT SOURCE
Туре	LED
Gross luminous flux	Depending on Mounting Accessories Lm
Color temperature	4000 K
Chromatic stability	MacAdam Step 2
Color Rendering Index	CRI>90
Power	Depending on Mounting Accessories W
Current	Depending on Mounting Accessories mA
DIMENSIONS	L90B10>55.000h
	LIGHTING FIXTURE   PHOTOMETRIC DATA
Lighting efficiency	92%
Lighting efficiency	0 Lm
Light beam angle	20°
Ø1.42in Ø1.57in (36mm) (40mm)	LIGHTING FIXTURE   ELECTRICAL DATA
• • • • • • • • • • • • • • • • • • •	Requires remote driver
3.30in (84mm)         Driver	Requires remote driver W
3.30in (84mm) Driver Power values of the system	W
3.30in (84mm) Power values of the system Frequency Dimping	W Depending on Mounting Accessories
3.30in (84mm) Driver Power values of the system	W
3.30in (84mm) Power values of the system Frequency Diamong	W Depending on Mounting Accessories Depending on Mounting Accessories
ACCESORIES	W Depending on Mounting Accessories Depending on Mounting Accessories OTHER DATA
ACCESORIES   ACCESORIES    ACCESORIES	W Depending on Mounting Accessories Depending on Mounting Accessories OTHER DATA DAMP
ACCESORIES	W Depending on Mounting Accessories Depending on Mounting Accessories OTHER DATA DAMP Included. For octogonal Junction box
3.30in (84mm)       Driver         Power values of the system       Frequency         ACCESORIES       Dimming         IXER DIFFUSER       ANTI-GLARE HONEYCOMB         LOUVER       Junction box cover         Junction box cover color	W Depending on Mounting Accessories Depending on Mounting Accessories OTHER DATA DAMP Included. For octogonal Junction box Textured white. Other finishing, please consult
ACCESORIES	W Depending on Mounting Accessories Depending on Mounting Accessories OTHER DATA DAMP Included. For octogonal Junction box Textured white. Other finishing, please consult Ø5.51 in I Ø140 mm
ACCESORIES  ACCESORIES  ACCESORIES  Driver  Power values of the system  Frequency  Dimming  Environmental location  Junction box cover  Junction box cover color  Junction box cover measurements  Swivel angle	W Depending on Mounting Accessories Depending on Mounting Accessories OTHER DATA DAMP Included. For octogonal Junction box Textured white. Other finishing, please consult Ø5.51 in   Ø140 mm 325°
ACCESORIES  ACCESORIES  ACCESORIES  ANTI-GLARE HONEYCOMB LOUVER  ANTI-GLARE HONEYCOMB LOUVER  ANTI-GLARE HONEYCOMB LOUVER  ANTI-GLARE HONEYCOMB LOUVER  ANTI-GLARE HONEYCOMB CONTRACT  ANTI-GLARE HONEYCOMB CONTRACT	W Depending on Mounting Accessories Depending on Mounting Accessories OTHER DATA DAMP Included. For octogonal Junction box Textured white. Other finishing, please consult Ø5.51 in   Ø140 mm 325° 355°
ACCESORIES	W Depending on Mounting Accessories Depending on Mounting Accessories OTHER DATA DAMP Included. For octogonal Junction box Textured white. Other finishing, please consult Ø5.51 in   Ø140 mm 325° 355° 0.76 lb   343 gr
ACCESORIES   ACCESORIES	W Depending on Mounting Accessories Depending on Mounting Accessories OTHER DATA DAMP Included. For octogonal Junction box Textured white. Other finishing, please consult Ø5.51 in   Ø140 mm 325° 355° 0.76 lb   343 gr 0.78 lb   423 gr
ACCESORIES	W Depending on Mounting Accessories Depending on Mounting Accessories OTHER DATA DAMP Included. For octogonal Junction box Textured white. Other finishing, please consult Ø5.51 in   Ø140 mm 325° 355° 0.76 lb   343 gr

IO is a LED spotlight miniaturised in a fixture that is so small that it fits on the palm of your hand. Designed for accent lighting applications, its small dimensions mean it can be fitted in display cabinets, shop windows and small places without generating an invasive presence on the scene.

JOKERLIGHT LLC 333 SE 2nd Av, Suite 2000 · Miami, FL 33131 (USA) info@jokerlight.com · jokerlight.com

PREMIO ADCV 2017 ORO 19-08-25 / 14:42

5Year





## PRODUCT

Model
Reference
Category


PRODUCT
Beam Mixer Diffuser
0805-01-00
Accessories
NOT SOLD SEPARATELY AFFECTS THE LIGHTING PARAMETERS

The Beam Mixer Diffuser is used to smooth beam artifacts caused by parabolic, Fresnel, or TIR lens collimators without significant broadening.

The unique mixing design provides superior far-field smoothing and color mixing with high on-axis brightness. Compared with traditional diffusers, it maintains higher central beam candlepower (CBCP), and produce less undesirable "field light" at higher angles.







## PRODUCT

Model
Reference
Colour
Category

PRODUCT	
Anti-glare Honeycomb Louver	
0806-00-00   WT   NT	
WT □ Textured white   NT ■ Textured black	
Accessories	
NOT SOLD SEPARATELY	<b>A</b>
AFFECTS THE LIGHTING PARAMETERS	$\odot$

Accessory made up of louver in the shape of a honeycomb panel to reduce glare and the effects of direct rays of vision.

